Test Report

Report Number: 919015-6-ST



DANISH TECHNOLOGICAL

INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 3 Init.: JNAS/JHA Order no.: 919015 Encl.: 2

Assignor: Four Design A/S, Faaborgvej 14, DK-5854 Gislev

Item: FourReal®A 74 + 90 Also covers FourReal®A 74 180 x 80 cm, FourReal®A 74 140 x 80 cm,

FourReal®A 90 140 x 80 cm

Sampling: The assignor confirms having selected the product. The product was forwarded by the

assignor and received at Danish Technological Institute on 18 August 2021.

Period: The test took place from 24 August 2021 to 31 August 2021.

Method: EN 15372:2016, Furniture - Strength, durability and safety - Requirements for non-domestic

tables

Test severity L2: General use: E.g. in general hotel, cafés, restaurants, public halls, banks,

bars, meeting rooms.

Additional information is given in enclosure B.

Test results: Passed.

The results are shown in enclosure A.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC

17025:2017) and in accordance with the General Terms and Conditions of Danish

Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

Place: Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute. The

date of issue appears from the digital signature.

Jacob Næsby Consultant



DANISH TECHNOLOGICAL INSTITUTE







Results

| Test No. | Test | Test Method | Loading | | Result | | |
|----------|---|-----------------------------|---|--------------------|--------|--|--|
| 5.1 | General requirements | | | | | | |
| 5.2.1 | Shear and squeeze points when setting up and folding | | | | | | |
| 5.2.2 | Shear and squeeze points under influence of powered mechanisms | | | | | | |
| 5.2.3 | near and squeeze points during use | | | | | | |
| 5.4.1-1 | Horizontal static load test | EN 1730, 6.2 | Test force, N Specified mass, kg Cycles | 400 50 10 | Passed | | |
| 5.4.1-2 | Vertical static load on main surface | EN 1730, 6.3.1 | Test force, N Cycles | 1250 10 | Passed | | |
| 5.4.1-3 | Additional vertical static load test where the main surface has a length >1600 mm | EN 1730, 6.3.2 | Test force, N Cycles | 1000 10 | Passed | | |
| 5.4.1-4 | Vertical static load on ancillary surface | EN 1730, 6.3.3 | Test force, N Cycles | 300 10 | N/A | | |
| 5.4.1-5 | Horizontal durability test | EN 1730, 6.4.1 and 6.4.2 | Test force, N Specified mass, kg Cycles | 300 50 15000 | Passed | | |
| 5.4.1-6 | Vertical durability test for cantilever and tables with central column only | EN 1730, 6.5 | Test force, N Cycles | 300 15000 | N/A | | |
| 5.4.1-7 | Vertical impact test for glass tabletops | EN 1730, 6.6.1 and 6.6.2 | Drop height, mm Cycles | 240 10 | N/A | | |
| 5.4.1-8 | Vertical impact test for all other tabletops | EN 1730, 6.6.1 and 6.6.3 | Drop height, mm Cycles | 180 10 | Passed | | |
| 5.4.1-9 | Drop test – This test is applicable for tables weighing more than 20 kg only | EN 1730, 6.9 | Drop height, mm Cycles | 50 6 | Passed | | |
| 5.4.1-10 | Stability under vertical load test | EN 1730, 7.2 | Main surface Ancillary surface | 400 200 | Passed | | |
| 5.4.1-11 | Stability for tables with extension elements | EN 1730, 7.3 | Test force, N | 200 | N/A | | |
| 6 | Information for use | | | | | | |
| A.3.2 | Durability of table with castors | EN 1730, 6.8 | Specified load, N Cycles | 20 2000 | N/A | | |

919015-6-ST Enclosure A, Page 2 of 3



Information provided by the Danish Technological Institute

Photograph of the received sample



Information required by EN 15372:2013

European Standards used:

EN 15372:2016 - Furniture - Strength, durability and safety - Requirements for non-domestic tables

EN 1730:2012 - Furniture - Tables - Test methods for the determination of stability, Strength and durability

Details of tested table:

| Model: | FourReal®A 74 + 90 | | | Type: | Table | | | | |
|------------|-----------------------|---------|---------|---------|--------|---------|---------|--|--|
| Width: | 800 mm | Length: | 1870 mm | Height: | 900 mm | Weight: | 47.8 kg | | |
| Materials: | Metal - particleboard | | | | | | | | |

Details of defects observed before testing:

None.

Details of any deviations from this standard:

None.

Any variation from the specified temperature range:

None.

Test result:

See enclosure A.

Name and address of the test facility:

Danish Technological Institute, Gregersensvej, Taastrup 2630, Denmark

Date of test:

2021-08-24 to 2021-08-31