





Four Design A/S Faaborgvej 14 DK-5854 Gislev Order no. 709628-1
Page 1 of 1
Appendices 2

Initials laha/prni/hbs

Gregersensvej DK-2630 Taastrup Tel. +45 72 20 20 00 Fax +45 72 20 20 19

info@teknologisk.dk www.teknologisk.dk

## **Test Report**

Material: Model: Four Sure 44 Loop

Type:	Chair							
Length:	530 mm	Width:	610 mm	Height:	830 mm			
Weight:	5,85 kg							
Materials:	Shell: 7 mm plastic Legs: Ø 16 mm metal tubes							

Sampling: The test material was sampled by the client and received at the Danish Techno-

logical Institute 05-08-2016

Method: EN 1022:2005 Domestic furniture - Seating - Determination of stability.

EN 16139:2013 Furniture - Strength, durability and safety - Requirements for

non-domestic seating.

Clauses 4.1, 4.2.3, 4.3.3, 5, 6.1.1, 6.1.2, 6.1.3, 6.1.5, 6.1.6, 6.1.8, 6.1.9, 6.1.10,

6.1.12, 6.1.13, 6.1.14, 6.1.15, 6.1.16

L1: General use: E.g. in office buildings, showrooms, public halls, function

rooms, cafés, restaurants, canteens, banks, bars.

Period: The testing was carried out from 08-08-2016 to 01-09-2016.

Result: Model Four Sure 44 Loop fulfils the requirements in EN 1022:2005 and

EN 16139:2013. Loading according to Test severity L1.

Individual results appear from Appendix 1.

Storage: The test material will be destroyed after 1 month, unless otherwise agreed.

Terms: The test has been performed according to the attached conditions, which are according to the guidelines

laid down by DANAK (The Danish Accreditation). The testing is only valid for the tested specimen. The

test report may only be extracted, if the laboratory has approved the extract

01-09-2016 Danish Technological Institute, Wood Technology, Taastrup

Lars Jeffers-Hansen
Ph. direct: +45 72 20 23 90
E-mail: laha@teknologisk.dk

Test responsible

Per Abildgaard Nielsen Ph. Direct: +45 72 20 23 07 E-mail: prni@teknologisk.dk

Co-reader



Order no. 709628-1

Appendix 1
Page 1 of 1

Initials laha/prni/hbs

## **Test of model: Four Sure 44 Loop**

Loading according to Test severity L1.

Test	Test Method	Cycles	Load	Result
4.1 General	EN 16139, 4.1			Passed
4.2.2 Shear and squeeze points under influence of powered mechanisms	EN 16139, 4.2.2			N/A
4.2.3 Shear and squeeze points during use	EN 16139, 4.2.3			Passed
4.3.2 Swivelling chairs	EN 1022			N/A
4.3.3 Non swivelling chairs	EN 1022			Passed
4.4 Rolling resistance of the unloaded chair	EN 16139, 4.4			N/A
5 Strength and durability requirements	EN 16139, 5			Passed
6.1.1 Seat static load and back static load test	EN 1728:2012, 6.4	10 10	Seat: 1600 N Back: 560 N	Passed
6.1.2 Seat front edge static load	EN 1728:2012, 6.5	10	Seat: 1300 N	Passed
6.1.3 Vertical load on back rests	EN 1728:2012, 6.6	10	Back: 600 N Seat: 1300 N	Passed
6.1.4 Foot rest static load test	EN 1728:2012, 6.8			N/A
6.1.4 Leg rest static load test	EN 1728:2012, 6.9			N/A
6.1.5 Arm rest sideways static load test	EN 1728:2012, 6.10	10	900 N	Passed
6.1.6 Arm rest downwards static load test	EN 1728:2012, 6.11	5	750 N	Passed
6.1.7 Vertical upwards static load on arm rests	EN 1728:2012, 6.13			N/A
6.1.8 Combined seat and back durability test	EN 1728:2012, 6.17	100000 100000	Seat: 1000 N Back: 300 N	Passed
6.1.9 Seat front edge durability test	EN 1728:2012, 6.18	50000	800 N	Passed
6.1.10 Arm rest durability test	EN 1728:2012, 6.20	30000	400 N	Passed
6.1.11 Foot rest durability test	EN 1728:2012, 6.21			N/A
6.1.12 Leg forward static load test	EN 1728:2012, 6.15	10	Edge: 500 N) (Seat: 1000 N)	Passed
6.1.13 Legs sideways static load test	EN 1728:2012, 6.16	10	Edge: 400 N) (Seat: 1000 N)	Passed
6.1.14 Seat impact test	EN 1728:2012, 6.24	10	240 mm	Passed
6.1.15 Back impact test	EN 1728:2012, 6.25	10	210 mm / 38°	Passed
6.1.16 Arm Impact Test	EN 1728:2012, 6.26	10	210 mm / 38°	Passed
6.1.17 Drop test (multiple seating)	EN 1728:2012, 6.27.1			N/A
6.1.18 Auxiliary writing surface static load test	EN 1728:2012, 6.14			N/A
6.1.19 Auxiliary writing surface durability test	EN 1728:2012, 6.22			N/A
7 Information for use	EN 16139, 7			N/A



Order no. 709628-1

Appendix 2
Page 1 of 1

Initials laha/prni/hbs

# **Test of model: Four Sure 44 Loop**

### **Photo**



The general conditions pertaining to assignments accepted by Danish Technological Institute shall apply in full to the technical testing or calibration at Danish Technological Institute and to the completion of test reports or calibration certificates within the relevant field.

### **Danish Accreditation (DANAK):**

DANAK is the national accreditation body in Denmark in compliance with EU regulation No. 765/2008.

DANAK participates in the multilateral agreements for testing and calibration under European co-operation for Accreditation (EA) and under International Laboratory Accreditation Cooperation (ILAC) based on peer evaluation. Accredited test reports and calibration certificates issued by laboratories accredited by DANAK are recognized cross border by members of EA and ILAC equal to test reports and calibration certificates issued by these members' accredited laboratories.

The use of the accreditation mark on test reports and calibration certificates or reference to accreditation, documents that the service is provided as an accredited service under the company's DANAK accreditation according to EN ISO IEC 17025.

#### **Construction Product Regulation:**

The Danish Technological Institute guarantees that employees carrying out tests to be used together with harmonized standards under notification no. 1235 according to EU regulation 305/2011, article 43, satisfy all the requirements made for capability, integrity and impartiality. You find the CPR here:

http://ec.europa.eu/growth/single-market/european-standards/harmonised-standards/construction-products/index\_en.htm

September 2015